

# 20FT DANGEROUS GOODS SINGLE SIDE DOOR

SCFU 022377 3  
25VA

MAXGROSS	19,850	KGS
TARE	43,760	LBS
PAYLOAD	3,520	KGS
	7,760	LBS
	16,330	KGS
	36,000	LBS
	35.2	CUM

NOTICE  
Bolt seal must be applied for transport

**AS1940  
CERTIFIED  
DETACHED STORE**

SCF

30  
1992-2022

BUND CAPACITY  
2,800 L

SCFU 022376 8  
25VA

MAXGROSS	19,850	KGS
TARE	43,760	LBS
PAYLOAD	3,520	KGS
	7,760	LBS
	16,330	KGS
	36,000	LBS
	35.2	CUM

NOTICE  
Bolt seal must be applied for transport

**AS1940  
CERTIFIED  
DETACHED STORE**

SCF

30  
1992-2022

SCFU 022341 2  
25VA

MAXGROSS	19,850	KGS
TARE	43,760	LBS
PAYLOAD	3,520	KGS
	7,760	LBS
	16,330	KGS
	36,000	LBS
	35.2	CUM

SCF

30  
1992-2022

SCFU 022326 4  
25VA

MAXGROSS	19,850	KGS
TARE	43,760	LBS

SCF

# 20ft Dangerous Goods Single Side Door

SCF's 20ft Dangerous Goods Single Side Door container is designed for the storage of dangerous goods where access is only required from one side. Ideally suited to businesses who are storing over 850L of Class 3 Flammables onsite.

## Key Features

- Flexible storage for chemical classes 3, 4.1, 4.3, 5.1, 6.1 and 8 (subject to MSDS compliance)
- Bunded to contain spillages
- Full single side opening access
- Galvanised steel floor grating
- Raised crossmembers to simplify spill cleanup

## Options

- Need something custom built? Call us on 131 132 to discuss your requirements.

## Details

Full side access allows this Dangerous Goods container to be easily loaded with a forklift. Small packaging items can also be safely loaded by individuals.

All SCF Dangerous Goods units are compliant with the relevant Australian Standards and come with galvanised steel flooring, bunding to contain spills, raised crossmembers to simplify the clean-up of spills and an emergency exit to ensure no one gets locked in.

Other key safety features include ventilation grills at the top and bottom of the side walls, and safety drain valve for easy cleaning.

Upon delivery, each customer will receive an Independent Certificate of Compliance.

## Specifications

### 20ft Dangerous Goods Single Side Door

*Specifications may vary*

#### Internal

Length (mm)	5,898
Width (mm)	2,309
Height (mm)	2,586

#### External

Length (mm)	6,058
Width (mm)	2,450
Height (mm)	2,896

## Weight

Tare (kg)	4,000
Payload (kg)	16,000
MGW (kg)	20,000



Top:  
Single side  
opening doors  
and end doors

Middle Left:  
Galvanised  
floor grates



Middle Right:  
Drain valve



Below:  
Glow in the  
dark  
emergency exit  
decals on end  
and side doors





SCFU 022377 3  
25VA

MAXGROSS	19,850	KGS
TARE	43,760	LBS
PAYLOAD	3,520	KGS
	7,760	LBS
CUB. CAP.	16,330	KGS
	36,000	LBS
	35.2	CUM

NOTICE  
Bolt seal must  
be applied  
for transport

**AS1940  
CERTIFIED**  
DETACHED STORE

SCF

30  
1992-2022

BOUND CAPACITY  
2,800 L

SCFU 022376 8  
25VA

MAXGROSS	19,850	KGS
TARE	43,760	LBS
PAYLOAD	3,520	KGS
	7,760	LBS
CUB. CAP.	16,330	KGS
	36,000	LBS
	35.2	CUM

NOTICE  
Bolt seal must  
be applied  
for transport

**AS1940  
CERTIFIED**  
DETACHED STORE

SCF

30  
1992-2022

SCFU 022341 2  
25VA

SCFU 022327 0  
25VA

MAXGROSS	19,850	KGS
	43,760	LBS

SCF

30  
1992-2022

SCFU 022326 4  
25VA

MAXGROSS	19,850	KGS
	43,760	LBS

SCF