

SCFU 897021 9

22K2

SCF

131 132

MPGM
ON UIC RAILWAYS
36000KG

ISO LIQUID TANK

131

ISO Liquid Tank

Our ISO liquid and acid tanks are suitable for a wide range of applications, including the intermodal transport of substances such as hazardous chemicals, ethanol, dangerous goods, fertilisers, liquid minerals, and non-dangerous goods cargoes.

Key Features

- Fully compliant with ISO, IMO and IMDG standards
- 14,000L - 26,000L capacities
- Supplied in current survey
- Suitable for use on road, rail and sea
- Variants available for the transportation and storage of food and chemicals

Options

- Safety handrails
- Steam heating and insulation
- Gantry platforms compliant to AS1957
- Additional loading hatches

Details

Our specialised ISO tanks cater to specific product or industry requirements and are custom designed to meet specific customer/cargo driven outcomes.

In addition to offering a wide range of sizes, we have both bottom and top discharge functions available.

Our liquid tanks' stainless steel shell and ISO frame make them ideal for gantry crane straddle lifting and side loader transportation.

Lining options are available for specific aggressive or corrosive cargo requirements.

Specifications

ISO Liquid Tank

Specifications may vary

Volume

Litres	14,000 - 26,000
--------	-----------------

m ³	14 - 26
----------------	---------

External

Length (mm)	6,058
-------------	-------

Width (mm)	2,438
------------	-------

Height (mm)	2,591
-------------	-------

Weight

Tare (kg)	2,500 - 3,500
-----------	---------------

Payload (kg)	32,500 - 33,500
--------------	-----------------

MGW (kg)	36,000
----------	--------

Top:
ISO frame and
lifting points



Middle Left:
Discharge valve



Middle Right:
Steam inlet and
outlet details



Below:
Breathe easy
indicator and
gantry





SCFU 897021 9

22K2



131 132

MPGM
ON UIC RAILWAYS
36000KG

